

# Network Video Recorder

NVR3264R-B



## Key Features


- 64-channel input
- Third-party IP cameras supported with ONVIF conformance
- Support 2-ch HDMI, 1-ch VGA, 1-ch CVBS, HDMI2 at up to 4K(3840x2160) resolution
- Up to 12 Megapixels resolution recording
- Support H.265/H.264 video formats
- Accurate retrieval, instant playback
- Support HDD hot swap with RAID 0, 1, 5, 6, 10 storage scheme configurable
- 8 SATA HDDs, Up to 8TB for each HDD
- Support various VCA detection alarm and VCA search
- Dewarping support for fisheye cameras
- Support N+1 Hot spare
- Support for 12V Power output
- Support for P2P, UPnP, NTP, DHCP, PPPoE
- Support for mobile client access

## Specifications


<b>Model</b>	NVR3264R-B
<b>Video/Audio Input</b>	
IP Video Input	64-ch
Two-way Audio Input	1-ch, RCA
<b>Network</b>	
Incoming Bandwidth	320Mbps
Outgoing Bandwidth	320Mbps
Remote Users	128
<b>Video/Audio Output</b>	
HDMI/VGA Output	HDMI1/VGA: 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz HDMI2: 4K (3840x2160) /60Hz, 4K (3840x2160) /30Hz, 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz
CVBS Output	1-ch, BNC
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-ch, RCA
Synchronous Playback	16-ch
<b>Decoding</b>	
Compression	H.265/H.264
Live view/ Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	3 x 12MP@25, 4 x 4K@30, 8 x 4MP@30, 16 x 1080P@30, 32 x 960P@25, 36 x 720P@30, 64 x D1
<b>Hard Disk</b>	
SATA	8 SATA interfaces
Capacity	Up to 8TB for each HDD
eSATA	1 eSATA interface
<b>Disk Array</b>	
Array Type	RAID 0, 1, 5, 6, 10
<b>External Interface</b>	
Network Interface	2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interfaces
Serial Interface	1 x RS232, 1 x RS485
USB Interface	Rear panel: 2 x USB2.0, 1 x USB3.0
Alarm In	16-ch
Alarm Out	4-ch
<b>General</b>	
Power Supply	100 ~ 240 VAC
Consumption ( without HDD )	≤ 20 W
Working Temperature	-10°C ~ + 55°C ( +14°F ~ +131°F )
Working Humidity	10% ~ 90%
Dimensions	86mm × 442mm × 531mm ( 3.4" × 17.4" × 19.9" )

Weight ( without HDD )	≤ 5.13 Kg (11.31 lb )
------------------------	-----------------------

## Dimensions



## Rear Panel



\*Product specifications and availability are subject to change without notice.